

H.264 4ch Standalone Digital Video Recorder

HDF1212

Features

Max. Recording 120fps(NTSC)/100fps(PAL)

Dynamic Recoding Schedule Functions (Time, Motion, Ala

4ch VideoLoop-Back & 1 VGA

Easy Control interface

: Front Key board / Remote controller / USB Mouse

Support SATA interface 1 HDD



Support DDNS server and Web server (with ActiveX)

Specifications

Model		HDF1212
[Video]		
Input	Composite	4CH, 1.0Vp-p, 75Ω
	Signal Format	NTSC / PAL
Output	Main Monitor	Composite 1CH BNC, 1CH VGA
	Output Level	Composite 1.0Vp-p , 75Ω
	Loopback Output	4CH BNC 1.0Vp-p, 75Ω
[Audio]		
Input & Output		1CH RCA type Line input / 1CH RCA type Line output
Audio Codec		ADPCM
[Recording]		
Compression Format		H.264 Baseline Profile
Compression Rate		4 Step Selectable
Frame Rate (NTSC/PAL)		D1 : 720x480 / 720x576 MAX.30 / 25fps (Channel 1 select only) Half D1 : 720x240 / 720x288 MAX.60 / 50fps (Channel 1, 2 select only) CIF : 360x240 / 360x288 MAX.120 / 100fps *Duplex mode CIF MAX. 60 / 50fps
Recording Mode		Time Continuous / Schedule / Motion / Sensor
Motion Detection		Each Channel Area selectable
[Display]		
Display Rate		Real time display per camera
Multiscreen Display		1 / 4 / Auto Sequence
[Playback]		
Display Mode		1 / 4
Play back Mode		Normal Playback, Various playback speed (forward and backward)
Search Mode		Archived data Search, Date/time, Calendar, Event
[Event]		
Sensor Input		4 TTL (terminal block NO/NC Programmable)
Alarm Output		2 TTL (terminal block NO/NC Programmable)
Pre-alarm Rdcording		Max. 30 sec
Post-alarm Rdcording		Max. 1 minute
[Language]		
Multi-Language		English,Japanese,Chinese,Russian,Korean
[Storage]		
Internal HDD	Interface Type	1 SATA Internal HDD
	Max HDD Capacity	Support 1T
	File System	Own File System
Internal ODD	Interface Type	-
[Backup]		
Data Exporting	USB	USB Memory, Clip copy for Quick Time (MOV)
	ODD	-
[Serial port]		
PTZ Camera control		1 RS-485
[Operation]		
Control Applications		Via Front Consol Control, USB Mouse, Remote Controller, TCP/IP (Network)
[Network]		
Remote Access Interface		Support Same Local Control interface
Remote Access Tool		ActiveX Base Web Live & Search / CNB CMS Access (Live, Setting, Search, Recoding, ETC.) / Event Alarm Callback, Remote Site System Check with CMS
Dynamic IP support		Yes, with CNB DDNS Server
Network Interface		10/100 base-T Ethernet (RJ-45)
System Time Sync		Support Network Time Protocol
[Other]		
Power		DC 12V, 3.33A, 40W
Dimensions (WxHxD)mm		351 x 71 x 275 (mm)