

CCTV Camera

HV-DBJ30-70



Effio-E + 673CCD
OSD Button in the cable




Features

- ◆ Vandalproof IR Dome Camera
- ◆ SONY Exview HAD CCD II (ICX672/3AKA)
- ◆ 36 pcs \varnothing 5mm IR-LED, IR Range 30M
- ◆ OSD/2D-DNR/BLC/MD/Privacy Masking
- ◆ 3-Axis Design, easy for installation
- ◆ Built-in 2,8 - 12mm Manual Zoom Lens



Size Chart



Specifications

Model Name	HV-DBJ30-70
Image Device	1/3" Exview HAD CCD II (ICX672/3AKA)
DSP Device	Effio-E (CXD4127GG,CXD4816GG)
Resolution	Color Mode: 650TVL; B/W Mode:700TVL
Picture Elements	PAL:976(H) \times 582(V) NTSC:976(H) \times 494(V)
IR Led & IR Range	36pcs \varnothing 5 IR Led; 30M IR Distance
Min. Illumination	0.001 Lux (F2.0)/ 0 Lux IR On
Lens Furnished	Built-in 2,8-12 mm Manual Zoom Lens
TV System	PAL/NTSC
Electronic Shutter	NTSC:1/60~1/100,000, PAL:1/50~1/110,000
S/N Ratio	More than 52dB
Gamma	0.45
Exposure	Auto
Shutter/ AGC	Auto/Manual
White Balance	ATW / User1/User2
Backlight	OFF/ON/BLC/ HLC
Pict Adjust	Mirror/Brightness/Contrast/Sharpness/Hue/Gain
ATR	ON/OFF
Motion Det	OFF/ON(Detect sense/ Area Sel)
Privacy Masking	OFF/ON (4 Zone)
Day/Night	True Day and Night (Auto/ Day / Night / Ext. D&N)
2D-NR	OFF/ON (Y/C level)
Camera ID	OFF/ON
Sync. System	Internal
Video Output	1 Vp-p / 75 Ohms

Power Supply	DC12V±10%; 320 mA
Operation Temperature	-10°C ~ +50°C RH95% Max
Dimension	∅135 x 86 mm
Weight	1000g

Design and specifications are subject to change without notice.