

# CCTV Camera

## HV-BSW-70




### Features

- ◆ Standard Box Camera
- ◆ SONY Exview HAD CCD II (ICX672/3AKA)
- ◆ High Resolution 650/700TVL
- ◆ OSD/2D-DNR/BLC/MD/Privacy Masking
- ◆ C/CS Mount; DC VD Lens Drive



*Effio-E + 673 CCD With OSD*

### Size Chart



### Specifications

Model Name	HV-BSW-70
Image Device	1/3" Exview HAD CCD II (ICX672/3AKA)
DSP Device	Effio-E (CXD4127GG,CXD4816GG)
Resolution	Color Mode: 650TVL; B/W Mode:700TVL
Picture Elements	PAL:976(H)×582(V) NTSC:976(H)×494(V)
Min. Illumination	0.001 Lux (F2.0)
Lens Mount	C/CS Mount; DC VD Lens Drive
TV System	PAL/NTSC
Electronic Shutter	NTSC:1/60~1/100,000, PAL:1/50~1/110,000
S/N Ratio	More than 52dB
Gamma	0.45
Exposure	Auto
Shuter/ AGC	Auto/Manual
White Balance	ATW / User1/User2
Backlight	OFF/ON/BLC/ HLC
Pict Adjust	Mirror/Brightness/Contrast/Sharpness/Hue/Gain
ATR	ON/OFF
Motion Det	OFF/ON(Detect sense/ Area Sel)
Peivacy Masking	OFF/ON (4 Zone)
Day/Nigh	True Day and Night (Auto/ Day / Night / Ext. D&N)
2D-NR	OFF/ON (Y/C level)
Camera ID	OFF/ON
Sync. System	Internal
Video Output	1 Vp-p / 75 Ohms
Power Supply	DC12V±10%

Operation Temperature	-10°C ~ +50°C RH95% Max
Dimension	65(W)x55(H)x125(L)
Weight	500g

*Design and specifications are subject to change without notice.*